



**MÉTAL DÉPLOYÉ EN ACIER MOTIF APLATI / EXPANDED METAL FLATTENED
PATTERN**

MODÈLE MODEL	LBS/100pi ²		A Intervalle Interval	B Intervalle Interval	C Ouverture Opening	D Ouverture Opening	E Épaisseur Thickness	F Largeur Width
	ORDINAIRE REGULAR	GALVANISÉ GALVANIZED						
3/16-22F	72	-	0.218	0.500	0.094	0.343	0.027	0.063
-20F	86	-	0.218	0.500	0.094	0.343	0.032	0.063
¼-20F	88	-	0.250	1.050	0.084	0.715	0.030	0.079
-18F	108	-	0.250	1.050	0.075	0.715	0.040	0.080
5/16-20F	54	-	0.333	1.030	0.203	0.813	0.032	0.075
-18F	95	-	0.333	1.030	0.172	0.813	0.040	0.099
½-20F	40	51	0.500	1.250	0.375	1.000	0.029	0.079
-18F	66	83	0.500	1.250	0.312	1.000	0.039	0.097
-16F	82	98	0.500	1.250	0.312	1.000	0.050	0.096
-13F	140	161	0.500	1.250	0.312	1.000	0.070	0.107
-13(188) F	275	299	0.500	1.250	0.250	1.000	0.070	0.188
¾-16F	51	57	0.923	2.100	0.750	1.750	0.048	0.111
-13F	75	88	0.923	2.100	0.688	1.781	0.070	0.106
-10(13) F	114	128	0.923	2.100	0.637	1.755	0.070	0.160
-9(10) F	171	188	0.923	2.100	0.563	1.688	0.120	0.165
1-16F	44	50	1.00	2.300	0.813	2.100	0.050	0.098
-14F	63	72	1.00	2.300	0.813	2.000	0.070	0.125
-12F	98	113	1.00	2.300	0.813	2.000	0.085	0.156
-10F	165	179	1.000	2.30	0.750	1.900	0.110	0.160
1 ½-16F	38	44	1.330	3.20	1.062	2.750	0.048	0.199
-13F	57	66	1.330	3.20	1.062	2.750	0.070	0.116
-12F	66	76	1.140	3.20	1.296	2.625	0.085	0.116
-9F	114	125	1.330	3.20	1.000	2.563	0.110	0.158
-10F	165	179	1.300	3.20	0.900	2.563	0.110	0.188