



MÉTAL DÉPLOYÉ EN ACIER MOTIF RÉGULIER
STEEL EXPANDED METAL REGULAR PATTERN

MODÈLE MODEL	LBS/100pi ²		A Intervalle Interval	B Intervalle Interval	C Ouverture Opening	D Ouverture Opening	E Épaisseur Thickness	F Largeur Width
	ORDINAIRE REGULAR	GALVANISÉ GALVANIZED						
3/32-24L	42	-	0.156	0.250	0.094	0.156	0.024	0.030
3/32-24H	63	-	0.156	0.250	0.063	0.156	0.024	0.045
3/16-22	56	-	0.203	0.500	0.110	0.313	0.030	0.047
3/16-20	90	-	0.203	0.500	0.080	0.313	0.036	0.063
¼-20	86	-	0.250	1.000	0.125	0.718	0.036	0.072
¼-18	114	-	0.250	1.000	0.110	0.718	0.048	0.072
5/16-20	57	-	0.333	1.000	0.250	0.750	0.036	0.063
5/16-18	104	-	0.333	1.000	0.188	0.688	0.048	0.094
½-20	43	51	0.500	1.200	0.438	0.938	0.036	0.072
½-18	70	88	0.500	1.200	0.438	0.938	0.048	0.088
½-16	86	104	0.500	1.200	0.375	0.938	0.030	0.087
½-13	147	174	0.500	1.200	0.312	0.938	0.090	0.096
½-3(.188)	282	310	0.500	1.200	0.250	0.800	0.090	0.188
¾-16	54	61	0.923	2.000	0.813	1.750	0.060	0.101
¾-13	80	94	0.923	2.000	0.750	1.688	0.090	0.096
¾-10(13)	120	134	0.923	2.000	0.750	1.625	0.090	0.144
¾-9(10)	180	198	0.923	2.000	0.688	1.562	0.135	0.150
1-16	47	54	1.000	2.250	0.938	2.000	0.60	0.087
1-14	78	90	1.000	2.250	0.875	1.563	0.074	0.125
1-12	96	110	1.000	2.250	0.907	1.563	0.105	0.109
1-10(170)	170	187	1.000	2.250	0.750	1.563	0.135	0.155
1-10H	200	221	1.000	2.250	0.750	1.563	0.135	0.180
1-7	412	453	1.000	2.250	0.576	1.563	0.138	0.275
1 ½-16	40	48	1.330	3.000	1.250	2.265	0.060	0.108
1 ½-13	60	68	1.330	3.000	1.188	2.500	0.090	0.105
1 ½-10(13)	79	90	1.330	3.000	1.188	2.500	0.090	0.138
1 ½-12	74	85	1.330	3.000	1.112	2.375	0.105	0.109
1 ½-9(10)	120	144	1.330	3.000	1.125	2.375	0.135	0.144
1 ½-10(170)	170	187	1.330	3.000	1.000	2.375	0.135	0.200
1 ½-10H	200	220	1.330	3.000	0.830	2.375	0.135	0.240
1 ½-6	250	275	1.330	3.000	1.110	2.375	0.198	0.203