



Plaques en acier /Steel plates

Épaisseur Thickness	lb/pied ² lb/ft ²		Épaisseur Thickness	lb/pied ² lb/ft ²
3/16	7.66		2-1/2	102.10
1/4	10.21		2-3/4	112.31
5/16	12.76		3	122.52
3/8	15.31		3-1/2	142.93
7/16	17.87		4	163.35
1/2	20.42		4-1/2	183.77
5/8	25.52		5	204.19
3/4	30.63		5-1/2	224.61
7/8	35.73		6	245.03
1	40.84		6-1/2	265.45
1-1/4	51.05		7	285.87
1-1/2	61.26		8	326.71
1-3/4	71.47		9	367.55
2	81.68		10	408.38

Plaques antidérapantes /Steel floor plates

Calibre Gauge	Épaisseur/p o Thickness/in ch	lb/pied ² lb/ft ²		Calibre Gauge	Épaisseur/p o Thickness/in ch	lb/pied ² lb/ft ²
16	0.059	3.750		5/16	0.315	13.800
14	0.079	5.250		3/8	0.375	16.300
1/8	0.125	6.150		1/2	0.500	21.450
3/16	0.188	8.700		5/8	0.625	26.580
1/4	0.236	11.250		3/4	0.750	31.680
				1	1.000	41.890

Tôles en acier laminé à chaud et à froid /Hot rolled and cold rolled steel sheet

Disponible : À chaud seulement⁽¹⁾ les deux⁽²⁾ à froid seulement⁽³⁾

Available : Hot rolled only⁽¹⁾ Both⁽²⁾ Cold rolled only⁽³⁾

Calibre Gauge	Épaisseur/po Thickness/inch	lb/pied ² lb/ft ²		Calibre Gauge	Épaisseur/po Thickness/inch	lb/pied ² lb/ft ²
7 ¹	0.1793	7.500		16 ²	0.0598	2.500
8 ¹	0.1644	6.875		18 ³	0.0478	2.000
9 ¹	0.1495	6.250		20 ³	0.0359	1.500
10 ²	0.1344	5.625		22 ³	0.0299	1.250
11 ²	0.1196	5.000		24 ³	0.0239	1.000
12 ²	0.1046	4.375		26 ³	0.0179	0.750
13 ²	0.0897	3.750		28 ³	0.0149	0.625
14 ²	0.0747	3.125		30 ³	0.0130	0.500

Tôles en acier galvanisé/Galvanized steel sheets

Calibre Gauge	Épaisseur/po Thickness/inch	lb/pied ² lb/ft ²		Calibre Gauge	Épaisseur/po Thickness/inch	lb/pied ² lb/ft ²
10	0.1382	5.781		20	0.0396	1.656
11	0.1233	5.196		22	0.0336	1.406
12	0.1084	4.531		24	0.0276	1.156
13	0.0934	3.906		26	0.0217	0.906
14	0.0785	3.281		28	0.0187	0.781
16	0.0635	2.656		30	0.0150	0.656
18	0.0516	2.156				