



**TUBES RONDS DE STRUCTURE EN ACIER SOUDÉ (HSS)
HOLLOW STRUCTURAL SECTION ROUNDS (HSS)**

PAROI ÉPAISSEUR WALL THICKNESS	0.065	0.083	0.095	0.100	0.110	0.120	0.125	0.134	0.150	0.188	0.210	0.238	0.250	0.313	0.375	0.438	0.500	0.625
Dia. Ext/Po OD/inch	Lb/pi – lb/ft																	
1.000	0.65	0.81	0.97			1.13												
1.050			0.95	1.01	1.10	1.13	1.23											
1.250		1.03	1.17	1.23			1.50	1.60										
1.315		1.09	1.30		1.40		1.59	1.68										
1.500	1.00	1.26	1.43				1.77											
1.660				1.67	1.82		2.05	2.17	2.42									
1.875				1.90			2.34											
1.900		1.61		1.92	2.10		2.38		2.80	3.43			4.41					
2.375		2.03		2.43			3.01		3.57	4.40			5.68					
2.500	1.69	2.14	2.44	2.78		3.05	3.17		3.77	4.65			6.02		8.51			
2.750				2.83														
2.875						3.53	3.67		4.37	5.40			7.01					
3.000	2.04	2.59			3.40		3.84	4.10	4.57	5.66			7.35					
3.500	2.39						4.51		5.37	6.66			8.69	10.66	12.52			
4.000	2.62	3.47		3.96		4.98	5.17	5.53	6.17	7.67	8.51		10.02	12.34	14.52			
4.250													10.68					
4.500						5.61	5.85	6.25	6.88	8.68		10.79	11.36	14.01	16.54			
5.000							6.84		7.78	9.67			12.69	15.69	18.52		24.03	
5.500						6.89				10.67			14.70		20.50			
5.563							7.10			10.80			14.20	17.60	20.80			
6.000							7.84		9.38	11.68			15.37	19.03	22.55			

[illegible]