



**MÉTAL DÉPLOYÉ EN ALUMINIUM MOTIF RÉGULIER
ALUMINUM EXPANDED SHEET REGULAR PATTERN**

MODÈLE MODEL	LBS/100pi ²	A Intervalle Interval	B Intervalle interval	C Ouverture Opening	D Ouverture Opening	E Épaisseur Thickness	F Largeur Width
3/16-032	28	0.203	0.500	0.080	0.313	0.032	0.060
5/16-032	22	0.330	1.000	0.219	0.690	0.032	0.080
5/16-051	35	0.330	1.000	0.188	0.920	0.051	0.080
1/2-051	25	0.500	1.200	0.375	0.937	0.051	0.080
1/2-081	41	0.500	1.200	0.375	0.937	0.081	0.080
3/4-051	17	0.923	2.000	0.812	1.750	0.051	0.109
3/4-081 LT	27	0.923	2.000	0.750	1.680	0.081	0.110
3/4-081 HVY	41	0.923	2.000	0.750	1.680	0.081	0.165
3/4-0.125	65	0.923	2.000	0.687	1.680	0.125	0.169
3/4-0.188	127	0.923	2.000	0.600	1.680	0.188	0.221
1 1/2-081	22	1.330	3.000	1.187	2.500	0.081	0.129
1 1/2-0.125	43	1.330	3.000	1.187	2.500	0.125	0.162
1 1/2-0.188	79	1.330	3.000	1.000	2.500	0.188	0.200

**MÉTAL DÉPLOYÉ EN ALUMINIUM MOTIF APLATI
ALUMINUM EXPANDED SHEET FLATTENED PATTERN**

MODÈLE MODEL	LBS/100pi ²	A Intervalle interval	B Intervalle Interval	C Ouverture Opening	D Ouverture Opening	E Épaisseur Thickness	F Largeur Width
3/16-032F	20	0.218	0.500	0.094	0.343	0.028	0.060
5/16-032F	20	0.333	1.020	0.188	0.813	0.030	0.082
5/16-051F	34	0.333	1.020	0.156	0.780	0.045	0.082
1/2-051F	24	0.500	1.270	0.312	1.000	0.040	0.091
1/2-081F	39	0.500	1.270	0.312	1.000	0.060	0.091
3/4-051F	16	0.923	2.125	0.750	1.812	0.040	0.122
3/4-081 LTF	25	0.923	2.125	0.687	1.750	0.070	0.134
3/4-081 HF	39	0.923	2.125	0.687	1.750	0.070	0.181
3/4-0.125F	62	0.923	2.125	0.625	1.750	0.095	0.187
1-0.188F	115	1.000	2.000	0.540	1.400	0.165	0.280
1 1/2-0.188F	72	0.923	2.125	0.575	1.600	0.170	0.200
1 1/2-0.081F	21	1.330	3.150	1.062	2.750	0.055	0.143
1 1/2-0.125F	41	1.330	3.150	1.000	2.750	0.095	0.181